

Smart IVR

EH-IA-A-28-F

16HDD 128CH 4K H.265+









Onvif



SLINK



IMS



APP



Modify Light Mode



Human Detection



Vehicle Detection



Retrograde



Absent Alarm

Introduction:

H.265+ 128CH IVR, support 128CH 4K IP camera input and output, support smart analysis IPC, 1 CH 4K/4CH 1080P/16 CH sub-code stream playback, 16 pcs HDD (max 10TB), 1CH VGA, 1 CH HDMI, support to upgrade IPC remote, modify IP camera address and light board mode, support alarm and audio, support RAID function and E-SATA port.

Features

- Support H.265+/H.265/H.264 dual stream decoding, 128 CH 4K IP camera input
- Support synchronous recording, remote monitoring, backup; up to 16CH 1080P video synchronous playback and multi-channel backwards playback
- Support to upgrade IPC online and upgrade IPC through memory
- Support to modify my company IP address and light board mode
- Support to add IPC manually or automatically in LAN
- Support 30min instant playback, 30s pre-record
- Standard ONVIF, SLINK, RTSP protocol
- Support DDNS, EMAIL, UPNP, NTP, P2P and other functions
- Support WEB, mobile phone monitoring, client, IMS monitoring
- Support external alarm; Two-way audio intercom
- Support our Smart IPC: target count, electric fence, human detection, retrograde detection, absent alarm
- Support IPC centralized management, including IPC parameter configuration, information export and import, real-time information acquisition and upgrade, etc
- Support channel grouping, preview tour
- Supports disk grouping quotas and disk group storage modes, support RAID0, RAID1, RAID5,RAID6,RAID10...matrix style
- Support network HDD (IPSAN, NAS), double password authentication
- Support network monitoring: network traffic, network delay packet loss test, network packet capture backup
- Support multiple language, micro-intelligence, capture playback

Specification

System	
Main Chipset	Hi3536
Operating System	Embedded Linux
Bandwidth	640M



Web : www.strategic.com.kw

Video Format		H.265+/H.265/H.264									
Video Resolution		4K/5MP/3MP/1080P/720P/D1									
Smart Functions		target count, electric fence, human detection, retrograde detection, absent alarm (need front end IPC supported)									
Record Mode		Manual, Schedule, Motion Detection, Timing, Alarm, Stop									
Playback		1CH 4K/4 CH 4K/9*3Mp/ 16CH 1080P									
Backup Mode		USB Device/Network									
Display mode:		64ch Digital (4000X3000) + 64ch Preview + 16ch Playback 128ch Digital (4000X3000) + 64ch Preview + 16ch Playback									
Video											
Normal N	/lode	64 CI	64 CH normal IPC								
Split	1	4	6	8	9	16	25	36	i	64	
Decode	4K	4K	4K+5*2mp	4K+7*2MP	2M	P 1080P	720P	D1		D1	
Normal N	/lode	128 CH normal IPC									
Split	1	4	6	8	9	16	25	36	64	128	
Decode	4K	4K	4K+5*2mp	4K+7*2MP	2MP	1080P 7	720P	D1	D1	D1	
Video, A	Video, Audio, Alarm										
Video Output		1 HDMI, 1 VGA									
Audio Input & Output		1 RCA in, 1 RCA out, HDMI audio									
Alarm Inp Output	out &	4 in 4 out									
Storage											
HDD		16 SATA, max 10TB HDD									
E-Sata		1									
Network											
Network Interface		2*RJ45 10M/100M/1000M self-adaptive LAN port									
Network Function		DDNS,EMAIL,UPNP,NTP,DHCP,IP Filter,PPPoE,P2P									
Smart Phone		iPhone, android									
External	Ports										
USB		3 USB Ports(2 USB2.0, 1USB3.0)									
RS232		N/A									
RS485		1									



Others						
Power Supply	ATX110-220V 300W 50-60Hz					
Power Consumption	≤ 50W(without HDD)					
Dimension	Equipment:431.5mm×521.2mm×133.2mm Packing:685mmX586mmX255mm					
Weight	N.W:15KG (without HDD) with package:17KG					
Outside Carton	1pcs/Carton; Dimension: 690mmX600mmX270mm, 17kg					

Size:





EnZhi HuaDaTong(ShenZhen)Digital Technology Co.,Ltd Add:6F,A-Big,No.4 North Area, ShangXue Science and Technology Industry, JiHua Road, BanTian, LongGnag District, ShenZhen, China www.ezhdt.com

Web: www.strategic.com.kw



^{*}Product pictures and technical data are only for reference, any update without prior notice, the final interpretation right belongs to ENZ.